

► EVERLITE







Ż	EVERLITE 03
	White







EVERLITE Closed 01 White

EVERLITE Closed 02 Black







DESCRIPTION

EVERLITE, is an occupational shoe made entirely of polymeric materials and with the following components:

- 🚔 Antistatic insert
- 🚔 Removable insole
- Ventilation holes both shoes and insole

SPECIFICATIONS



Antistatic 1 Promotes the dissipation of accumulated static

Super-light 2 This shoe is produced in Everlite[™], a material with great durability and comfort and is remarkably light.

Upper Protection 3 Avoids the entrance of liquids to the inside of the shoe.

Breathable 4 Regulates the temperature and humidity of the foot *

Shock Absorption 5 Reduces the occurrence of micro-lesions in tendons, bones and joints and the feeling of tired legs.

Anti-slip (6) The sole is designed to reduce the risk of slipping.

Removable Insole A removable insole, flexible, breathable and machine washable up to 50°C.

Unisex Style designed to be worn by men and women.

Washable The footwear can be machine washable up to 50°C

Extra Protection Due to EVERLITE Closed being completely closed, protects the foot against liquid spillage and contamination in controlled environments. **

Closed Heel Additional support for the moments that require extra agility.

Portuguese Shoes Footwear 100% developed and made in Portugal.

USERS

00

EVERLITE is ideal for uses where prolonged standing or walking may tend to induce foot discomfort or lower body fatigue, especially in:

Hospitals and other Healthcare Institutions **Cosmetic/Beauty Companies Pharmaceutical Industry Cleaning Companies** Food Industry **Catering Industry**



experience with EVERLITE.

CARE AND CLEANING

Wash: Machine washable up to a maximum temperature of 50°C. Cold sterilization with chlorine, sodium hypochlorite or hydrogen peroxide. Dry: Wipe with a cloth or dry at room temperature.

TECHNICAL STANDARD

CE Technical file of auto-certification based on 89/686/EEC directive. (CE)

EN ISO 20347: 2012 Personal protective equipment – Occupational footwear, class II.

EN ISO 20347: 2012 (6.2.2.2) Antistatic footwear. EN ISO 20347: 2012 (6.2.4) Energy absorption of seat region.

SATRA TM 144: 2011 Friction (slip resistance) of footwear and floorings.

TECHNICAL SPECIFICATIONS

Heat resistance -machine washable up to a maximum of 50°C Slip-resistant Resistant to abrasion Resistant to detergents Resistant to lactic Acid Resistant to liquids (such as infiltration of blood) Resistant to chemicals Resistant to saltwater Resistant to animal fat

MATERIALS

EN ISO

SATRA

The material used in this shoe is called Everlite™ in it's exapanded form. Everlite™ material provides odor resistance, inhibits bacterial and fungal growth and is non-toxic.

ATTENTION

EVERLITE resists several washings at 50°C in washing machine. It is not recommended the use of bleaching agents during washing machine cycles at 50°C.

The resistance of Everlite™ material to washing depends on several factors:

- Type of detergent
- Concentration
- Cycles' duration
- Temperature
- Physical stress during the cycles

* Not applied to EVERLITE Closed.

** Only applies to EVERLITE Closed.

Made and designed by: WOCK[®] 2015 by Procalçado S.A.



Price: € 31,00 (excluding VAT)

RIJKSWEG 10 - 2880 BORNEM - BELGIUM www,arseus-medical,be